

CURRENT LISTING OF CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

- 1 1. (Withdrawn) A computer-implemented method comprising:
2 assigning information stored on a computer a plurality of clearance levels;
3 assigning each smart badge within a set of smart badges one of the clearance levels;
4 using a wireless beacon to detect which smart badges are located within a predefined
5 boundary;
6 identifying a lowest clearance level assigned to the smart badges within the boundary;
7 and
8 providing access to that sub-set of the information having a clearance level no higher than
9 the lowest identified clearance level.
- 1 2. (Withdrawn) The method of claim 1 further comprising:
2 defining those smart badges within the boundary as a set of visible smart badges; and
3 updating the set of visible smart badges in response to a change in smart badge visibility
4 status.
- 1 3. (Withdrawn) The method of claim 2 further comprising:
2 recalculating the lowest clearance level in response to the change in smart badge
3 visibility status.
- 1 4. (Withdrawn) The method of claim 2 further comprising:
2 recording the smart badge visibility status of each smart badge within an activity log.
- 1 5. (Withdrawn) The method of claim 1 wherein providing includes:
2 providing access to smart badge wearers assigned to the smart badges.
- 1 6. (Withdrawn) The method of claim 2 further comprising:
2 preventing access to the information when the smart badge visibility status is set to
3 invisible for a predetermined timeout.

- 1 7. (Withdrawn) The method of claim 1 further comprising:
2 writing data items to the smart badges.
- 1 8. (Withdrawn) The method of claim 7 further comprising:
2 pre-reading the data items from the smart badges during idle periods.
- 1 9. (Withdrawn) The method of claim 1 further comprising
2 defining a badge removal confidence level indicating whether each smart badge has been
3 continuously worn by corresponding assigned smart badge wearers.
- 1 10. (Withdrawn) The method of claim 1 further comprising:
2 assigning an expiration period to each of the smart badges; and
3 de-authenticating and erasing all data stored on a smart badge whose expiration period
4 has been exceeded.
- 1 11. (Withdrawn) The method of claim 1 wherein the using element includes:
2 configuring the predefined boundary by varying a sensitivity level of the wireless beacon.

12. (Withdrawn) A method for context-aware computer management comprising:
assigning database information a plurality of clearance levels;
assigning each smart badge within a set of smart badges one of the clearance levels;
using a wireless beacon to detect which smart badges are located within a predefined physical boundary;
identifying a lowest clearance level assigned to the smart badges within the boundary;
providing access to that sub-set of the database information having a clearance level no higher than the lowest identified clearance level on a computer located within the predefined physical boundary;
defining those smart badges within the boundary as a set of visible smart badges;
updating the set of visible smart badges in response to a change in smart badge visibility status; and
recalculating the lowest clearance level in response to the change in smart badge visibility status.

13. (Previously Presented) A computer-usable medium embodying computer program code for context-aware computer management, comprising:
assigning database information a plurality of clearance levels;
assigning each smart badge within a set of smart badges one of the clearance levels;
using a wireless beacon to detect which smart badges are located within a predefined physical boundary;
identifying a lowest clearance level assigned to the smart badges within the boundary;
and
providing access to that sub-set of the database information having a clearance level no higher than the lowest identified clearance level on a computer located within the predefined physical boundary.

14. (Previously Presented) The computer-usable medium of claim 13 further comprising:
defining those smart badges within the boundary as a set of visible smart badges; and
updating the set of visible smart badges in response to a change in smart badge visibility status.

1 15. (Previously Presented) The computer-usable medium of claim 14 further comprising:
2 recalculating the lowest clearance level in response to the change in smart badge
3 visibility status.

1 16. (Previously Presented) The computer-usable medium of claim 13 wherein providing
2 includes:
3 providing access to the database information to smart badge wearers assigned to the
4 smart badges.

1 17. (Previously Presented) The computer-usable medium of claim 14 further comprising:
2 preventing access to the database when the smart badge visibility status is set to invisible
3 for a predetermined timeout.

1 18. (Previously Presented) The computer-usable medium of claim 13 further comprising
2 defining a badge removal confidence level indicating whether each smart badge has been
3 continuously worn by corresponding assigned smart badge wearers.

1 19. (Previously Presented) The computer-usable medium of claim 13 further comprising:
2 assigning an expiration period to each of the smart badges; and
3 de-authenticating and erasing all data stored on a smart badge whose expiration period
4 has been exceeded.

1 20. (Withdrawn) A system for context-aware computer management comprising:
2 means for assigning database information a plurality of clearance levels;
3 means for assigning each smart badge within a set of smart badges one of the clearance
4 levels;
5 means for using a wireless beacon to detect which smart badges are located within a
6 predefined physical boundary;
7 means for identifying a lowest clearance level assigned to the smart badges within the
8 boundary;
9 means for providing access to that sub-set of the database information having a clearance
10 level no higher than the lowest identified clearance level on a computer located within the
11 predefined physical boundary;
12 means for defining those smart badges within the boundary as a set of visible smart
13 badges;
14 means for updating the set of visible smart badges in response to a change in smart badge
15 visibility status; and
16 means for recalculating the lowest clearance level in response to the change in smart
17 badge visibility status.

1 21. (Previously Presented) A system for context-aware computer management comprising:
2 a database, including information differentiated by a plurality of clearance levels;
3 a first wireless beacon;
4 a set of smart badges, detected by the first beacon to be within a predefined boundary,
5 each badge assigned one of the clearance levels;
6 a computer located within the boundary;
7 a system service module, coupled to the beacon, for identifying a lowest clearance level
8 assigned to the smart badges within the boundary; and
9 a software application, coupled to the service module and the database, for providing
10 access to that sub-set of the information within the database having a clearance level no higher
11 than the lowest identified clearance level on the computer.

- 1 22. (Original) The system of claim 21, wherein the first beacon includes:
2 a wide angle RF beacon.
- 1 23. (Previously Presented) The system of claim 21, further comprising:
2 a second diffuse IR beacon, coupled to the service module, limited to detecting smart
3 badges within the predefined boundary.
- 1 24. (Original) The system of claim 21, wherein the smart badges include:
2 biometric sensors for detecting when a smart badge has been removed from an assigned
3 smart badge wearer.
- 1 25. (Previously Presented) The system of claim 21, wherein the service module
2 defines those smart badges within the boundary as a set of visible smart badges, and
3 recalculates the lowest clearance level in response to a change in a visibility status.
- 1 26. (Previously Presented) The system of claim 21, wherein the application logs smart badge
2 wearers assigned to visible smart badges onto the computer.
- 1 27. (Withdrawn) The method of claim 1, wherein providing access to the sub-set of
2 information comprises providing access to the sub-set of information stored on the computer
3 located within the predefined boundary.
- 1 28. (Withdrawn) The method of claim 1, wherein the wireless beacon comprises a first
2 wireless beacon to communicate with the smart badges, the method further comprising:
3 using a second wireless beacon to communicate with the smart badges,
4 wherein detecting which smart badges are located within the predefined boundary is
5 based on the first and second wireless beacons.

1 29. (Withdrawn) The method of claim 28, wherein using the second wireless beacon
2 comprises using the second wireless beacon to communicate with smart badges within the
3 predefined boundary and to communicate with smart badges outside the predefined boundary
4 through one or more blocking objects defining the predefined boundary, and
5 using the first wireless beacon comprises using the first wireless beacon to communicate
6 with smart badges within the predefined boundary, wherein the first wireless beacon is blocked
7 from communicating with smart badges outside the predefined boundary by the one or more
8 blocking objects.

1 30. (Withdrawn) The method of claim 29, wherein using the first wireless beacon comprises
2 using an infrared beacon, and wherein using the second wireless beacon comprises using a radio
3 frequency beacon.

1 31. (Withdrawn) An article comprising a computer-usable medium containing program code
2 that when executed cause a computer to:
3 store plural sub-sets of information, each sub-set of information associated with one of
4 plural clearance levels;
5 use at least a first wireless beacon to communicate with plural badges within a predefined
6 region, each of the plural badges associated with one of the plural clearance levels;
7 determine a lowest clearance level from among the clearance levels associated with the
8 badges in the predefined region; and
9 provide access to one or more sub-sets of the information having one or more respective
10 clearance levels no higher than the determined lowest clearance level.

1 32. (Withdrawn) The article of claim 31, wherein providing access to the one or more
2 sub-sets of the information comprises displaying the one or more sub-sets of the information
3 having the one or more respective clearance levels no higher than the determined lowest
4 clearance level.

1 33. (Withdrawn) The article of claim 31, wherein the program code when executed cause the
2 computer to further:

3 use a second wireless beacon to communicate with the plural badges in the predefined
4 region and to communicate with one or more badges outside the predefined region,

5 wherein the first wireless beacon is able to communicate with the plural badges within
6 the predefined region but is unable to communicate with the one or more badges outside the
7 predefined region; and

8 determining the badges that are within the predefined region based on the first and second
9 wireless beacons.

1 34. (Withdrawn) The article of claim 31, wherein the program code when executed cause the
2 computer to further:

3 receive a parameter from each of the badges, the parameter indicating a confidence level
4 that the respective badge has been worn continuously by a user.

1 35. (Withdrawn) The article of claim 31, wherein the program code when executed cause the
2 computer to further:

3 re-determine the lowest clearance level as badges enter or leave the predefined region.

1 36. (Withdrawn) A system comprising:

2 storage to store sub-sets of information associated with corresponding plural clearance
3 levels;

4 a first wireless beacon to communicate wirelessly with badges within a predefined
5 region, each of the badges associated with one of the plural clearance levels;

6 a module to identify a lowest clearance level from among the clearance levels of the
7 badges within the predefined region; and

8 software to provide access to one or more sub-sets of information in the storage having
9 one or more clearance levels no higher than the identified lowest clearance level.

1 37. (Withdrawn) The system of claim 36, further comprising:
2 a second wireless beacon to communicate wirelessly with badges within the predefined
3 region and at least one badge outside the predefined region,
4 wherein the first wireless beacon is unable to communicate with the at least one badge
5 outside the predefined region,
6 the module to detect the badges that are within the predefined region based on the first
7 and second wireless beacons.

1 38. (Withdrawn) The system of claim 37, wherein the second wireless beacon comprises a
2 radio frequency beacon, and the first wireless beacon comprises an infrared beacon.